



1711163-1 | CABLE CAT7 PIMF600 LSZH 23AWG
Copper Twisted Pair Cable, Category 7, shielded, white

Body Features

Cable Configuration	F/FTP
Conductor Material	Copper
Jacket Color	White
Insulation Material	PE
Shield Type	Individual foiled pairs/Overall foil

Configuration Features

Number of Conductors	8
Number of Pairs	4

Dimensions

Overall Outside Diameter	7.400 mm 0.291 in
Conductor Diameter	.546 – .61 mm
Length	500.000 m 1640.420 ft
Wire Diameter	6.050 mm 0.238 in
Wire Size (CMA)	.258 mm ² 23 AWG

Industry Standards

Flammability Rating	LSZH
---------------------	------

Operation/Application

Halogen Free	Yes
--------------	-----

Packaging Features

Packaging Method	Reel
Packaging Quantity	500

Product Availability

Region	Australia/New Zealand EMEA
--------	------------------------------

Product Type Features

Product Type	Cable
Cable Style	Simplex
Cable Type	Twisted Pair
Performance Category	Category 7
Product Classification	Cable - ISO/IEC Category

1711163-1 | CABLE CAT7 PIMF600 LSZH 23AWG

Shielded	Yes
Wire/Cable Type	Twisted Pair

Usage Conditions

Operating Temperature Range -20 – 60 °C

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant