



6536967-2 | FOMM50 LEAD OM3 1.8MZ LC/DPX-SC/DPX 2M

## Body Features

Boot Color (Left)	Beige
Boot Color (Right)	Black
Boot Type (Left)	Bend limiting
Boot Type (Right)	Bend limiting
Cable Color	Aqua
Connector Color (End A)	Beige
Connector Color (End B)	Beige

## Configuration Features

Number of Fibers	2
Exit Angle to Exit Angle	180° to 180°
Number of Connectors (End A)	2
Number of Connectors (End B)	2

## Dimensions

Assembly Length	2.00 m   6.56 ft
Outside Cable Diameter	.071 x .142 in   1.8 x 3.6 mm

## Industry Standards

Flammability Rating	LSZH (Low Smoke Zero Halogen)
---------------------	-------------------------------

## Product Availability

Region	Australia/New Zealand   EMEA
--------	------------------------------

## Product Type Features

Product Type	Patch Cord (simplex/duplex)
Connector Type (End A)	LC UPC
Connector Type (End B)	SC UPC
Fiber Type	OM3
Connector Style (End A)	Duplex
Connector Style (End B)	Duplex
Ferrule Material	Ceramic
Fiber Cable Buffering	Tight buffer
Fiber Cable Type	Duplex, dualzip
Fiber Diameter	50/125 µm
Optical Mode	Multimode
Polarity	Pair Flipped

## Signal Characteristics

Insertion Loss, maximum (End A)	0.30 dB
Insertion Loss, maximum (End B)	0.30 dB
Return Loss, minimum	30 dB

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
RoHS 2011/65/EU	Compliant

## \* Footnotes

Assembly Length	Assembly length includes the breakout lengths
Return Loss, minimum	Applies to 1310nm and 1550nm wavelengths