

Type N Male Right Angle / SMA Male

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-NMRSMA002	14.00	12.60	11.20	CALL
		4.0ft (1.2m)	CA-NMRSMA004	15.00	13.50	12.00	CALL
		10.0ft (3.0m)	CA-NMRSMA010	18.00	16.20	14.40	CALL
		20.0ft (6.1m)	CA-NMRSMA020	23.00	20.70	18.40	CALL

Type N Male Right Angle / TNC Male

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-NMRTMA002	18.00	16.20	14.40	CALL
		4.0ft (1.2m)	CA-NMRTMA004	19.00	17.10	15.20	CALL
		10.0ft (3.0m)	CA-NMRTMA010	22.00	19.80	17.60	CALL
		20.0ft (6.1m)	CA-NMRTMA020	27.00	24.30	21.60	CALL

Reverse Polarity BNC Plug / Type N Male

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RBPNA002	19.50	17.55	15.60	CALL
		4.0ft (1.2m)	CA-RBPNA004	20.50	18.45	16.40	CALL
		10.0ft (3.0m)	CA-RBPNA010	23.50	21.15	18.80	CALL
		20.0ft (6.1m)	CA-RBPNA020	28.50	25.65	22.80	CALL

Reverse Polarity SMA Plug / Type N Male

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSPNMA002	16.00	14.40	12.80	CALL
		4.0ft (1.2m)	CA-RSPNMA004	17.00	15.30	13.60	CALL
		10.0ft (3.0m)	CA-RSPNMA010	20.00	18.00	16.00	CALL
		20.0ft (6.1m)	CA-RSPNMA020	25.00	22.50	20.00	CALL
200-Series Center Conductor: Solid copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyethylene Operating Temperature: -40°C - +80°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSPNME002	18.10	16.29	14.48	CALL
		4.0ft (1.2m)	CA-RSPNME004	19.20	17.28	15.36	CALL
		10.0ft (3.0m)	CA-RSPNME010	22.50	20.25	18.00	CALL
		20.0ft (6.1m)	CA-RSPNME020	28.00	25.20	22.40	CALL
400-Series Center Conductor: Copper clad aluminum Min. Bend Radius: 1.0" (25.4mm) Jacket: Polyethylene Operating Temperature: -40°C - +80°C	.405 in. (10.3mm)	2.0ft (0.6m)	CA4NMRSF002	24.00	21.60	19.20	CALL
		10.0ft (3.0m)	CA4NMRSF010	30.00	27.00	24.00	CALL
		20.0ft (6.1m)	CA4NMRSF020	37.50	33.75	30.00	CALL
		25.0ft (7.6m)	CA4NMRSF025	41.25	37.13	33.00	CALL
		30.0ft (9.0m)	CA4NMRSF030	45.00	40.50	36.00	CALL
		50.0ft (15.2m)	CA4NMRSF050	60.00	54.00	48.00	CALL
400UF-Series Center Conductor: Stranded bare copper Min. Bend Radius: 1.0" (25.4mm) Jacket: Black Thermoplastic Elastomer Operating Temperature: -40°C - +85°C	.405 in. (10.3mm)	5.0ft (1.5m)	CA-NMRSFH005	19.35	18.19	17.03	CALL
		10.0ft (3.0m)	CA-NMRSFH010	25.35	23.83	22.31	CALL
		15.0ft (4.6m)	CA-NMRSFH015	31.35	29.47	27.59	CALL
		25.0ft (7.6m)	CA-NMRSFH025	43.35	40.75	38.15	CALL
		50.0ft (15.2m)	CA-NMRSFH050	73.35	68.95	64.55	CALL
		75.0ft (22.9m)	CA-NMRSFH075	103.35	97.15	90.95	CALL
100.0ft (30.5m)	CA-NMRSFH100	133.35	125.35	117.35	CALL		

Reverse Polarity SMA Plug / Type N Female

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSPNFA002	14.50	13.05	11.60	CALL
		4.0ft (1.2m)	CA-RSPNFA004	15.50	13.95	12.40	CALL
		10.0ft (3.0m)	CA-RSPNFA010	18.50	16.65	14.80	CALL
		20.0ft (6.1m)	CA-RSPNFA020	23.50	21.15	18.80	CALL

Reverse Polarity SMA Plug / Type N Female Bulkhead

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSPNFA002	18.00	16.20	14.40	CALL
		4.0ft (1.2m)	CA-RSPNFA004	19.00	17.10	15.20	CALL
		10.0ft (3.0m)	CA-RSPNFA010	22.25	20.03	17.80	CALL
		20.0ft (6.1m)	CA-RSPNFA020	27.25	24.53	21.80	CALL

Reverse Polarity SMA Plug / Reverse Polarity SMA Jack

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSPRSJA002	18.00	16.20	14.40	CALL
		4.0ft (1.2m)	CA-RSPRSJA004	19.00	17.10	15.20	CALL
		10.0ft (3.0m)	CA-RSPRSJA010	22.00	19.80	17.60	CALL
		20.0ft (6.1m)	CA-RSPRSJA020	27.00	24.30	21.60	CALL

Reverse Polarity SMA Jack / Reverse Polarity TNC Plug

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
195-Series Center Conductor: Solid bare copper Min. Bend Radius: 0.50" (12.7mm) Jacket: Polyvinyl Chloride (CMP Grade for Plenum Rated) Operating Temperature: -20°C - +60°C	.195 in. (5.0mm)	2.0ft (0.6m)	CA-RSJRTPA002	17.00	15.30	13.60	CALL
		4.0ft (1.2m)	CA-RSJRTPA004	18.00	16.20	14.40	CALL
		10.0ft (3.0m)	CA-RSJRTPA010	21.00	18.90	16.80	CALL
		20.0ft (6.1m)	CA-RSJRTPA020	26.00	23.40	20.80	CALL

